

Data Sheet



No hassle warranty

NO HASSLE

No waiting.

No shipping charges.

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

MT-10 Moisture Meter

Measure moisture content for wall board, wood or other building materials to determine places of harmful mold growth or unseen water damage.

Typical application also include checking moisture of concrete slab and wood before installation of floors, determining wood moisture content during drying process, and checking wood moisture before material is used for woodworking applications.

- Checks for moisture content in wood, paper or cardboard and building materials such as sheetrock, concrete, mortar, plaster etc...
- Measurement Ranges:
 - Wood/ Paper: 8 ~ 60%
 - Building Material: 0.3 2.0%
 - Temperature: 0°C ~ 40°C or 32°F ~ 99°F
- Used in indoor air quality applications for detecting moisture in the walls, floors and ceilings stimulating mold growth
- **LCD** Display provides moisture or temperature measurement
- Three color LED provides quick moisture indication:
 - Green "air-dry" conditions
 - Yellow increased moisture
 - Red excess moisture
- Backlight for operation in dark areas
- Low battery indication
- Auto power off





MT-10 Mini-vane Anemometer

Data Sheet

Specifications

8 ~ 60%
0.3-2.0%
0 ~ 40°C or 32 ~ 99°F
0.1%
0.01%
0.1°C / 0.2°F
±2%
±0.1%
±1°C/±2°F
Symbol " "shown on the display (Automatic Power-Off)
9V, 6F22
Temperature 0°C ~ 40°C (32°F to 104°F)
Relative Humidity < 85%
Temperature -10°C ~ -50°C (14°F to -58°F)
Relative Humidity < 85%
145(L) × 60(W) × 31(H)mm (5.73 x 2.37 x 1.21 in)
Approx. 95g (0.37 lb)