



Commercial Recovery Machine

FM3700

Features

- 3/8" ports for faster, high-volume refrigerant recovery
- Recovers ALL commonly used refrigerants, including R-410A (Puron™)
- 550 PSI high pressure cut-off, high pressure gauges
- High performance compressor
- Rugged and reliable



FM3700 Heavy Duty Commercial Recovery Unit

The FM3700 is designed for use in commercial refrigerant recovery applications. The 3700's industrial strength, one horsepower, twin piston compressor enables the unit to recover refrigerant vapor at up to four pounds per minute and liquid up to eight pounds per minute, directly through the compressor.

SPECIFICATIONS

Refrigerants	All Refrigerants except R-11, R-113 and R-123
Power Source	115 VAC 50/60 Hz, 230 VAC 50/60 Hz, 100 VAC 50/60 Hz
Compressor	1 horsepower twin piston, high performance, oil-less
Vacuum Rating	13" Hg+
High Pressure Limit	550 PSI
Recovery Rate	.50 - 4.0 lbs./min. vapor, 8.0 lbs./min. liquid
Auto 80% Tank Shut Off	Optional
Self Purging System	No hose changes
Weight	47 lbs.
Dimensions	12" x 14.25" x 8.75"

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
2000-3700	FM3700 Commercial Recovery Unit
2002-0081	80% Shut-Off option

Also Available from Bacharach



Refrigerant Leak Detector
Tru Pointe

- A patented Heated Diode Detector at a Corona Discharge detector price
- Instantly detects all refrigerants
- Innovative sensor replacement design
- 11 to 20 hours of continuous operation
- Easy to use, hand-held operation



Refrigerant Recovery Machine
Stinger

- Greater condenser capacity provides faster recovery on the hottest days
- Large, easy to read gauges indicate pressure and vacuum so you know when recovery is completed
- New, dual valve compressor provides faster recovery rates
- High pressure copper tubing is used throughout the unit
- Compressor is driven by a powerful, 0.8 horsepower motor
- Full steel frame in rugged polymer case



Dual Purpose Leak Detector
Informant 2

- Two instruments in one – has the ability to detect both refrigerants and combustible gases
- Sensors are interchanged quickly and easily
- Utilizes patented heat diode sensor technology to detect refrigerants
- Utilizes patented semiconductor sensor technology to detect combustible gases
- Automatic zero and background compensation enables leaks to be found quickly, even in contaminated areas

Complimentary Tools



Charging Scale



Sling Psychrometer



R-410A Manifold Set



Tubing Cutter



Flaring, Swaging & Cutting Kit

Distributed By:

Contact:
Industrial Process Measurement, Inc.
3910 Park Avenue, Unit 7
Edison, NJ 08820
732-632-6400
support@instrumentation2000.com
<http://www.instrumentation2000.com>

Technical Training for Heating & Cooling



Bacharach is a registered trademark of Bacharach, Inc.
©April, 2005, Bacharach, Inc., all rights reserved. All information is subject to verification
Product Bulletin-7004 04/05 2M BI
Printed in U.S.A.