



Indoor Environmental Quality Monitor IEQ Chek™

IEQ Chek[™] Features & Benefits:

- Versatile handheld instrument with flexible 7-sensor capacity
- Ideal for indoor environmental quality measurements
- On-board sensors for temperature and relative humidity; add up to 5 additional plug-and-play 'smart' sensors
- · Large multi-line LCD graphic display
- · Stores over one million data points with SD flash card
- Optional data download kit with USB connection to PC and IQ Chek™ software



Multi-Sensor Flexibility

Bacharach's IEQ Chek $^{\text{TM}}$ is a versatile multi-sensor instrument for measuring, monitoring and recording indoor environments for air quality diagnosis. With its 7-sensor capacity, the new IEQ Chek $^{\text{TM}}$ measures temperature, relative humidity, and up to 5 additional plug-and-play 'smart' sensors, including carbon dioxide (CO₂), carbon monoxide (CO), oxygen (O₂), formaldehyde (HCHO), total volatile organic compounds (TVOCs), nitrogen dioxide (NO₂), sulfur dioxide (SO₂), ammonia (NH₃), hydrogen sulfide (H₂S) and combustible gases. Available with or without an on-board pump for sampling the air, the IEQ Chek $^{\text{TM}}$ has a large multi-line backlit LCD display with simultaneous viewing of all installed sensors, battery life, pump indicator and calibration status. Sophisticated, yet simple to use, the instrument has the capability to record and store over one million data points on a SD flash card with the option to download the data via USB connection to a PC using Bacharach's IQ^{TM} Chek software.

Bacharach's IEQ Chek™ line offers maximum features, flexibility and functionality for indoor environmental quality monitoring, HVAC measurements, ASHRAE/ANSI compliance, process operations in non-hazardous environments and medical/lab applications. The IEQ Chek™ is an ideal tool for identifying energy saving opportunities in over-ventilated spaces, determining if carbon dioxide (CO₂) build-up is due to insufficient ventilation, pinpointing the presence of carbon monoxide generated from vehicles or appliances, and measuring other air contaminants such as formaldehyde or volatile organic compounds found in paints, chemicals or cleaning products.

IEQ Chek™ Specifications

Gases Detected: Carbon Dioxide (CO₂), Carbon Monoxide (CO), Oxygen (O₂), Formaldehyde (HCHO), Total Volatile Organic Compounds (TVOCs),

Nitrogen Dioxide (NO2), Nitric Oxide (NO), Sulfur Dioxide (SO2), Ammonia (NH3), Hydrogen Sulfide (H2S) and Combustible Gases

Non-Dispersive Infrared (NDIR), Electrochemical, Photoionization Detector (PID)

 CO_2 CO₂ CO2 CO₂ CO2 02 0-5,000 0-10,000 0-5% vol 0-20% vol 0-100% 0-25% vol Range: vol maa mag 1% Resolution: 1 ppm 1 ppm 0.01% 0.01% 0.1% Accuracy: $\pm 2\%$ over range @ 68° F (20° C) / 1 bar pressure ±0.1% vol over range

Other Measurements:

Detection Principle:

Range:

Resolution:

Accuracy:

Temperature 23° F to 131° F (-5° C to 55° C) / 0.1° Resolution Relative Humidity 0-99.9% Non-Condensing / 0.1% Resolution

Dimensions: 7.75" L x 3.87" W x 3.06" D (19.7 cm x 9.8 cm x 7.8 cm)

Weight: 20 oz (567 g) including batteries
Housing: Rugged ABS/Polycarbonate

Display: Large, Multi-line Backlit LCD Digital Display. Simultaneously Displays all Installed Sensors, Battery Life, Pump Indicator and

Calibration Progress Bar

Alarm: 80 dB Audible Alarm for One User-Selected Setpoint

Operating Temperature Range: 41° F to 122° F (5° C to 50° C)
Operating Humidity Range: 0 - 99% RH Non-Condensing

 Data Storage:
 > 1 Million Data Points - Stored to SD Flash Card

 Data Download:
 Optional USB Connection to PC w/ IQ Chek™ Software

Power: 3 AA NiMH Rechargeable Batteries; (3 AA Alkaline Batteries can be User Installed); 6 VDC Power Adapter (N.Am. Plug or Intl. Pigtail

w/IE320-C13 Socket)

Run Time:
Approvals:
CE Mark: IS EN61010-1:2001; EM/RFI EN 50270:2006
Warranty:
Instrument - Two Years; CO₂ Sensor - 1 Year

Kit Contents: Instrument comes with 3 AA NiMH rechargeable batteries, charger/adapter, calibration adapter (pump versions only) and user manual

IEQ Chek™ Part Number Configurator 15AB-CDEF

| | | Choose 1 | Choose 1 | Choose 1 | Choose 1 | Choose 1 | Choose 1 |
|---|---|--|---------------------------------|---------------------|---------------------|----------------------|---------------------------------------|
| 1 | 5 | A | В | С | D | E | F |
| | | 0 = No sensor | 0 = No sensor | 0 = No sensor | 0 = No sensor | 0 = No sensor | 0 = Do not use |
| | | 1 = CO ₂ (0-5,000 ppm) | 1 = IR Combustible (0-5%) | 1 = CO | 1 = CO | 1 = CO | 1 = Diffusion, no DataLogging |
| | | 2 = CO ₂ (0-10,000 ppm) | 2 = TVOC (0-300 ppm) | 2 = 0 ₂ | 2 = 0 ₂ | 2 = 0 ₂ | 2 = Pump, no DataLogging |
| | | 3 = CO ₂ (0-5% vol) | 3 = TVOC (0-50 ppm) | 3 = NH ₃ | 3 = NO ₂ | 3 = \$02 | 3 = Diffusion w/ DataLogging |
| | | 4 = CO ₂ (0-20%) | | 4 = N0 | 4 = HCHO | 4 = H ₂ S | 4 = Pump w/ DataLogging |
| | | 5 = CO ₂ (0-100% vol) | | | | | 5 = Diffusion, no DL, ext. battery |

6 = Pump, no DL, ext. battery

7 = Diffusion w/ DL, ext. battery

8 = Pump w/ DL, extended battery

Distributed By:

Contact: Industrial Process Measurement, Inc. 3910 Park Avenue, Unit 7 Edison, NJ 08820 732-632-6400 support@instrumentation2000.com http://www.instrumentation2000.com

IEQ Chek[™] Common Configurations *All configurations include Temp and RH

 1510-0002
 CO2 (0-5,000 ppm), Pump

 1510-0004
 CO2 (0-5,000 ppm), Pump, DataLogging

 1510-1001
 CO2 (0-5,000 ppm), CO, Diffusion

 1510-1002
 CO2 (0-5,000 ppm), CO, Pump

 1510-1003
 CO2 (0-5,000 ppm), CO, Diffusion, DataLogging

 1510-1004
 CO2 (0-5,000 ppm), CO, Pump, DataLogging

1510-1302 CO₂ (0-5,000 ppm), CO, NO₂, Pump **1510-1304** CO₂ (0-5,000 ppm), CO, NO₂, Pump, DataLogging **1510-1403** CO₂ (0-5,000 ppm), CO, HCHO, Diffusion,

DataLogging CO₂ (0-5,000 ppm), TVOC (0-300ppm), CO, Pump, Ext. Battery, DataLogging

1520-0002 CO₂ (0-10,000 ppm), Pump

1520-0003 CO₂ (0-10,000 ppm), Diffusion, DataLogging

1530-0001 CO₂ (0-5%), Diffusion **1540-0002** CO₂ (0-20%), Pump

IEQ Chek™ Accessories & Replacement Parts

1509-0001 IQ Chek™ DataLogging Option (Includes

2GB flash card, cable, software & SD card reader)

1509-0002 Rugged Transport Case for IEQ Chek™

1509-0003 10" probe w/30" of sample hose for IEQ Chek™

1509-0005 IEQ Chek™ Externally-mounted, NiMH Battery Pack (required when CO2 / TVOC sensors are installed in

the same instrument)

1509-0008 IEQ Chek™ Replacement NiMH Batteries (pkg. of 3)





