

# Data sheet

## Function Generators Models 4010A & 4011A



### 4010A 2 MHz Function Generator

- 0.2 Hz to 2 MHz
- Sine, Square, Triangle, Pulse & Ramp output
- Variable duty cycle
- Variable DC offset
- Variable amplitude output plus 20dB attenuator
- 20Vpp output into open circuit (10Vpp into 50 Ωs)
- cUL certified



### 4011A 5 MHz Function Generator

- 0.5 Hz to 5 MHz
- Sine, Square, Triangle, Pulse, & Ramp output
- Coarse and Fine tuning
- 4 digit LED display
- Variable duty cycle
- Variable DC offset
- Variable amplitude output plus 20dB attenuator
- 20Vpp output into open circuit (10Vpp into 50 Ωs)
- cUL certified



Specifications	4010A	4011A
<b>Frequency Characteristics</b>		
Waveforms	Sine, Square, Triangle, $\pm$ Pulse, $\pm$ Ramp	
Range	0.2 Hz to 2 MHz in 7 ranges	0.5 Hz to 5 MHz in 7 ranges
Resolution	NA	4 digits
Dial Accuracy	$\pm$ 5% typical	NA
Tuning Range	10:1 Does not apply	Coarse, 10:1 Fine $\pm$ 5% of coarse setting
Variable Duty Cycle	15:85:15 cont variable	15:85:15 Cont variable
Operating Modes	Normal, VCG	
<b>Output Characteristics</b>		
Impedance	50Ω $\pm$ 10%	
Level	20 V p-p Open circuit, 10V p-p into 50Ω	
Amplitude	Variable, 20 dB range typical	
Attenuation	-20 dB $\pm$ 1dB	
DC Offset	Preset $\pm$ 0.1 V typ Variable: $\pm$ 10V open-circuit $\pm$ 5 into 50Ω	
Distortion	$\leq$ 4% @ 1 kHz	$\leq$ 3% @ 1 kHz
Flatness	$\leq$ 5% (.45 dB)	
Symmetry	0.5 Hz to 100 KHz $\leq$ 2%	
Risetime (Into 50Ω)	$\leq$ 120 nS	$\leq$ 20 nS
Linearity	$\geq$ 98% to 100 KHz, $\geq$ 95% to 2 MHz	
<b>TTL Output</b>		
Level	0.8V to 2.4V	
Rise time (0.8V to 2.9V)	$\leq$ 50 nS	$\leq$ 20 nS
Duty Cycle	50% typical	
<b>CMOS Output</b>		
Max. Frequency	2 MHz	
Level	4V to 14V $\pm$ 0.5 p-p cont. variable	
Rise Time	$\leq$ 120 nS	
<b>Input VCG</b>		
Input Voltage	0-10V $\pm$ 1V causes a 100:1 frequency change	
Impedance	10KΩ $\pm$ 5%	
<b>Frequency Counter INT</b>		
Accuracy	NA	Time Base Acy $\pm$ 1 count
Time Base Accuracy	NA	$\pm$ 10 PPM (23°C $\pm$ 5°C)
<b>General</b>		
Display	NA	4 digit LED
Power Source	120/230 VAC $\pm$ 10%, 50/60 Hz, internal jumper selectable	
Dimensions (H x W x D)	4.5 x 11.75 x 10.375", (114 x 298 x 264 mm)	
Weight	4 lbs. (1.8 kg)	
<b>Two Year Warranty</b>		
Supplies Accessories	Output cable with BNC to alligator clips, Instruction Manual, Line Cord	
Optionmal Accessories	Carrying Case (not included): LC-40, TIFG kit	

Contact:  
Industrial Process Measurement, Inc.  
3910 Park Avenue, Unit 7  
Edison, NJ 08820  
732-632-6400  
support@instrumentation2000.com  
<http://www.instrumentation2000.com>

Technical data subject to change  
© B&K Precision Corp. 2012  
v031212

