

CT2678

15 MHz Passive Oscilloscope Probe

Datasheet

Fixed 1x attenuation, 5 mm, cable length 12...

Description

General purpose series 15 MHz, 1x fixed attenuation oscilloscope probe.

- 15 MHz (-3 dB) bandwidth
- 300 V CAT II

Features & Benefits:

- Snap-Locking Sprung Hook
- Easily replaceable tip
- Large accessory set
- Meets IEC 61010-031
- RoHS compliant

Accessories included: 15 cm Ground Lead, Replacement Tip, Black Snap-on Sprung Hook, Tip Insulator, IC Tip, BNC Adapter & Coding Rings.

The HighPerformance family is a high quality, general purpose set of 5mm Passive Voltage Oscilloscope probes. They are excellent replacement probes for all makes and models of oscilloscopes.



Technical data subject to change.

© Cal Test Electronics 2018.



All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

Specifications

Type	5 mm Passive Voltage
Bandwidth	15 MHz
Attenuation	1x
Input Impedance	1 megaohms
Input Capacitance	46 pF
Output Impedance	1 megaohms
Risetime	27 ns
IEC Rating	300 V CAT II
Compensation	
Cable Length	1.2 m
Readout Actuator	
Operating Temperature (degrees)	0 to +50 C
Humidity	85% RH or less (at 35 C)
RoHS (2011/65/EU)	Compliant

Specifications are subject to change without notice.

Technical data subject to change.

© Cal Test Electronics 2018.



Contact:
Industrial Process Measurement, Inc.
3910 Park Avenue, Unit 7
Edison, NJ 08820
732-632-6400
support@instrumentation2000.com
<http://www.instrumentation2000.com>