

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, appliances, light fixtures, electrical cables and similar products.



**DIELECTRIC STRENGTH TESTER (HIPOT)  
MODEL AV-25DV-5**

OUTPUT	Adjustable 0 -2500 V ac @ 5 mA (0-2750 V ac @ open circuit).
TRANSFORMER	Rated 500 VA Short Duty Cycle
VOLTMETER	DPM 0-2500 V ac @ 5 mA (0-2750 V ac @ open circuit) Accuracy: $\pm 2\%$ Of full scale
TRIP CURRENT	Fixed @ 5 mA $\pm 5\%$
INPUT	120 V 60 Hz
INDICATORS	4 Lights (Power-on, High-Voltage-on, Fault and Line-Fault)
CONTROLS	One on/off switch, one fuse, one reset push-button, one high voltage adjust-knob and safety device for faulty power-outlet.
LEADS	One input Line-Cord 2 meter (6 ft) long, one ground lead c/w a clip and one high-voltage lead c/w a clip 2 meter (6 ft) long.
SIZE	30W x 25D x 18H cm (12W x 10D x 7H) Inches
WEIGHT	9.5 kg (21 Lb)

Contact:  
Industrial Process Measurement, Inc.  
3910 Park Avenue, Unit 7  
Edison, NJ 08820  
732-632-6400  
support@instrumentation2000.com  
<http://www.instrumentation2000.com>