

This tester is ideal for testing: control panels, small transformers, small electrical motors, home-appliances, electronic-ballasts, switching power supplies and similar equipment. To meet CSA & UL Specifications.
It is housed in a Flame retardant polypropylene copolymer resin cabinet.



PORTABLE DIELECTRIC STRENGTH TESTER MODEL AV/DV-25VA-95/10-SD-01

INPUT	120 V 60 Hz Single-Phase
OUTPUT	Adjustable: 0-2500 V ac & dc @ 95 mA ac & 10 mA dc
TRANSFORMER	Rated @ 500 VA short duty cycle
VOLTMETER	0-2500 V ac & dc Accuracy: $\pm 2\%$ of full scale
AMMETER	0-100 mA ac & 0-10 mA dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 95 mA ac & 10 mA dc $\pm 5\%$
INDICATORS	4 Lights (Power-on, High-Voltage-on, Fault and Line-Fault)
CONTROLS	One on/off switch, one fuse, one ac/dc meters-switch, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet
LEADS	One input line-cord, one ground lead and one high-voltage lead c/w clips. Each is 2 meters (6 ft.) long
SIZE	40W x 30D x 17H cm (15.8W x 12.4D x 6.8 H inches)
WEIGHT	6.8 kg (15 lb)

Contact:
Industrial Process Measurement, Inc.
3910 Park Avenue, Unit 7
Edison, NJ 08820
732-632-6400
support@instrumentation2000.com
http://www.instrumentation2000.com