

DIELECTRIC STRENGTH TESTER/HIPOT

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, home-appliances, lighting , electrical cables and components.



MODEL DV-25V-10-SD-01 PORTABLE C/W A COVER

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 10 mA
TRANSFORMER	Rated 500 VA Short Duty Cycle
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 10 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead c/w a clip and one high-voltage lead c/w a clip. Each is 2 meters (6 ft) long.
SIZE	30W x 25D x 15H cm (12W x 10D x 6H inches)
WEIGHT	5 kg (11 lb)

Contact:
 Industrial Process Measurement, Inc.
 3910 Park Avenue, Unit 7
 Edison, NJ 08820
 732-632-6400
 support@instrumentation2000.com
<http://www.instrumentation2000.com>