



Measuring the World Around You

M110 Data Sheet

Mini Light **Meter**



Description:

With this meter you can measure illuminance from fluorescent, metal halide, high-pressure sodium and incandescent sources. Giving units in both Lux and Foot-candles, the M110 is durable, reliable, and easy to use. The M110 features:

Features:

- Overload indicator: LCD screen will show "OL" on the upper left-hand corner
- Low battery indicator "4-----"
- Sampling rate: 2.5 times per second for digital display
- Spectral response close to CIE luminous spectral efficiency
- Cosine angular corrected
- According to JIS C 1609:1993 and CNS 5119 general A class Specifications
- Lux or foot-candle units
- Many applications include: Warehouses, factories, office buildings, restaurants, schools, library, hospitals, photographic, many video, parking garages, museums, art galleries, stadiums, building security
- Data hold (HOLD)
- Maximum/Average/Minimum Hold (MAX/MIN)
- Zero adjustment (ZERO)
- Auto power off and disable function
- Auto ranging

Applications:

- Warehouse & Factory Lighting
- Photography and Videography
- Energy Audits
- Museums & Art Galleries 3³/₄
- Stadium lighting





(F



ANAHEIM SCIENTIFIC

Technical Specifications

| Display | 4000 count, maximum display 3999 |
|---|---|
| Sensor | Silicon photodiode and filter |
| | |
| Measuring Range | 400,4000, 40000,400000 Lux |
| | 40,400,4000,40000 Foot-candles |
| Angle deviation from cosine characteristics | 30° ±2% |
| | 60 ° ±6% |
| | 80 ° ±25% |
| Power Supply | 2 batteries 1.5V AAA |
| Accuracy | ±3% ±3Lux(0~500Lux), ±3%(above 501 Lux) |
| | (Calibrated to standard incandescent lamp |
| | 2856°K) |
| | 8% other visible light source |
| Battery life | About 200 hours |
| Operating Conditions | 5ºC ~ 40ºC, 0%~ 80%RH, ≤2km altitude |
| | |
| Storage Conditions | -10ºC ~ 60ºC, 0%~ 70%RH |
| Dimensions | 133(L) x 48(W) x 23(D) mm |
| | 5.3(L) x 1.9(W) x 0.2(D) inch |
| Weight | 80g (including battery) |
| Accessories | User's manual, carrying case, 2x 1.5V battery |
| Warranty | Limited two-year warranty |
| - | · · · · · · · · · · · · · · · · · · · |

Includes:

- Meter
- User Manual
- Carrying Case
- 2x 1.5V AAA Batteries

This instrument conforms to:

- EN61326-1 (2006)
- IEC 61000-4-2(2008, IEC 61000-4-3(2006) + (2007)
- CE



Contact: Industrial Process Measurement, Inc. 3910 Park Avenue, Unit 7 Edison, NJ 08820 732-632-6400 support@instrumentation2000.com http://www.instrumentation2000.com