

Conductivity Meter



Description:

The P772 is a wide-range, pocket-sized conductivity meter perfect for use in field environments. Having a rugged, waterproof housing, and replaceable electrodes, this meter will give long durable service. With 10 $\mu\text{S}/\text{cm}$ resolution and $\pm 2\%$ FS accuracy, you will have high quality results at your fingertips. Automatic temperature compensation (ATC) adjusts for changes in conductivity due to temperature.

Features:

- Resolution: 10 $\mu\text{S}/\text{cm}$
- High accuracy: $\pm 2\%$ Full Scale
- Measures 0~19990 $\mu\text{S}/\text{cm}$
- Rugged waterproof housing that floats (meets IP57 standards)
- Compact size fits easily into your pocket
- Automatic temperature compensation
- Replaceable electrodes
- Large 21 x 18 mm LCD display
- Easy 1-point calibration with included calibration solution
- Comes ready-to-go with two long-life 3-V Lithium batteries

Applications:

- Agriculture/Gardening/Husbandry
- Anti-freeze recycling
- Aquariums
- Boilers
- Chemical industry
- Cooling towers
- Water treatment/Drinking Water
- Fish farming
- Food industry
- Hydroponics
- Laboratory usage
- Plating industry
- Swimming pools & Spas



WARRANTY



Specifications

Range	0~19990 μ S/cm
Resolution	10 μ S/cm
Accuracy	\pm 2% Full Scale
Operating Environment	5°C to 50°C 0 to 90% R.H.
Storage Environment	5°C to 50°C 0 to 90% R.H.
ATC Range	5°C to 50°C
Power	Two 3-V Lithium (CR2032) batteries
Expected Battery Life	100 hours continuous
Display	3 digit 21 x 18 mm LCD (.8 x .7")
Dimensions	33.5 x 170 mm (1.3 x 6.7")
Calibration	Manual, 1 point, via screw trim pot.
Weight	85 g (3 oz)
Housing	ABS IP57

Includes:

- P772 Cond. Meter
- Two 3V Batteries
- Instructional manual
- Calibration solution
- Calibration screwdriver
- Gift Box

This instrument conforms to:

- **EN61326:** Electrical equipment for measurement, control and laboratory use.
- **IEC61000-4-2:** Electrostatic discharge immunity test.
- **IEC61000-4-3:** Radiated, radio-frequency, electromagnetic field immunity test.
- **IEC61000-4-8:** Power frequency magnetic field immunity test.

