

DLRO100 Series Digital low resistance ohmmeters



- CAT IV 600 V AC / 500 V DC for safe operation
- Lightweight 100 A battery powered unit for portability
- High noise immunity for stable readings
- Smooth DC Output for circuit breaker testing
- IP54 for protection against dust and moisture whilst testing
- Save, download and delete results (100X/H variants)
- Remote operation, Bluetooth® and asset/result tagging (100H variants)

DESCRIPTION

A significant addition to the comprehensive range of Megger Low Resistance Ohmmeters, DLRO100 enables low resistance measurement, across multiple applications, in areas without access to mains power. The integral Li-Ion battery supplies a constant 100 A current for up to 200 Manual/Auto tests to enable enhanced productivity in remote locations. With a focus on user safety, advanced design features ensure the safe operation of the instrument in the most adverse conditions, including a CAT IV 600 V AC / 500 V DC safety rating in accordance with IEC61010. The rugged design, intuitive interface and IP54 (lid open) rating ensure reliability and ease of use in the most arduous of conditions.


Test Modes

The **Manual test** mode allows the user to initiate the test procedure once the probes are in contact with the object under test. Once the TEST button is depressed the TEST lamp will illuminate and the instrument will undertake a single test to verify the resistance of the test object.

In **Auto mode** the user selects the desired current, connects the current test leads and as soon as the potential leads are connected a test will start

automatically. To repeat a test, simply break contact with the potential probes and remake contact.

In **Continuous mode** the user connects the test leads and presses the TEST button, initiating the test procedure. The instrument will continue to test, updating the display after each new test cycle, until the TEST button is pressed or the test procedure times out.



A new tough adjustable clamp has been designed to ensure flexibility in many applications and provides a good connection with the test piece.

Test Leads:

Standard test leads, with separate Current and Potential, or Kelvin, combining both Current and Potential in one clamp, are available as optional accessories in 5 m, 10 m and 15 m lengths. All test leads are CAT IV 600 V AC / 500 V DC safety rated.

DLRO100 Series Digital low resistance ohmmeters

History of 'Ducter' testing

For over 100 years the 'Ducter test' has been used to describe a simple test for measuring very low contact resistances and "Ducter", which is still used as a trade mark, was the name originally given to the low resistance ohmmeter manufactured by Megger. The name Ducter was registered by Megger in June 1908 and 'Ducter' has since become the industry standard.

APPLICATION

The need for accurate low resistance measurement is well known and very diverse. Typical applications include:

Utilities and Service Contractors – commissioning new installations and regular maintenance testing of:

- Switchgear and circuit breaker contact resistance
- Busbar and cable joints
- Wire and cable resistance
- Lightning conductor bonding

Original Equipment Manufacturer – detecting manufacturing defects:

- Production test of circuit breakers – contacts and joints
- Production test of high voltage switchgear
- Production test of welded joints and connections

Transport – manufacturing and maintenance:

- Railway rolling stock ground connections and manufactured joints
- Railway lines and conductor rails – commissioning and maintenance
- Aircraft frame bonds and static control circuits

SPECIFICATIONS		
Measurement range	0.1 $\mu\Omega$ – 1.999 Ω	
Resolution	0.1 $\mu\Omega$	
Noise rejection	Differential 100 mV @ 50-60 Hz on Test Leads	
DC output	Smooth DC	
IP rating	IP54 Lid open / IP65 Lid closed	
Operating temperature range	-20°C (-4°F) up to +50°C (+122°F)	
Storage temperature range	-30°C (-22°F) up to +70°C (+158°F)	
Humidity	<85% R.H. non-condensing	
Battery life	200 single 100 A tests or up to 2x 10 minutes continuous 100 A output	
Battery type	User replaceable Li-ion battery pack	
Battery charge time	Full charge in 2.5 Hrs from flat	
Maximum output voltage	2 V (battery), 3 V (AC)	
EMC	IEC61326-1	
Safety	IEC61010 CAT IV 600 V AC / 500 V DC up to 6500 ft CAT IV 300 V up to 13000 ft	
Dimensions	15 x 11 x 7 inches	
Weight	17 lbs	
Accuracy		
Current setting	Resistance range	Accuracy
50 – 110 A	0 – 100.00 m Ω	Typical \pm (0.2% + 0.2 $\mu\Omega$) Max. \pm (0.2% + 0.8 $\mu\Omega$)*
11 – 49 A	10 $\mu\Omega$ – 100.00 m Ω	Typical \pm (0.2% + 0.5 $\mu\Omega$) Max. \pm (0.2% + 2.0 $\mu\Omega$)*
10 A	10 $\mu\Omega$ – 1000.0 m Ω	Typical \pm (0.2% + 1.0 $\mu\Omega$) Max. \pm (0.2% + 2.5 $\mu\Omega$)*
Added operational uncertainty for harsh environmental conditions (85% RH, -20°C (-4°F) up to +50°C (+122°F)):		
Current setting#	Resistance range	Accuracy
50 – 110 A	0 – 100.00 m Ω	\pm (0.0% + 0.0 $\mu\Omega$)
11 – 49 A	10 $\mu\Omega$ – 100.00 m Ω	\pm (0.0% + 1.0 $\mu\Omega$)
10 A	10 Ω – 1000.0 m Ω	\pm (0.1% + 2.0 $\mu\Omega$)
# Actual test current may be limited by maximum output voltage		
* $k = \pm 4\sigma$		
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG Inc., and is used under licence.		

DLRO100 Series Digital low resistance ohmmeters

FEATURES AND BENEFITS				
	DLRO100			
FEATURES	EB	XB	HB	BENEFITS
CAT IV 600 V AC / 500 V DC up to 6561 ft CAT IV 300 V up to 13123 ft	■	■	■	On all test terminals for safe operation
Lightweight 100 A battery powered unit	■	■	■	Easily portable – 7.9 Kg (17 lbs) with battery
High noise immunity	■	■	■	For stable readings in noisy environments
Smooth DC Output	■	■	■	Circuit breaker testing
IP54 Lid open IP65 Lid closed	■	■	■	For protection against ingress during operation (lid open) and storage (lid closed)
Li-ion battery	■	■	■	Always ready to test with a Li-ion fast charge battery – 2.5 hours charge time from fully discharged. Works from an AC supply if the battery is fully discharged. Battery capacity – 200 single tests or up to 2x 10 mins continuous 100 A output for extended use
100 A Manual, Auto and Continuous test	■	■	■	Quick selection of test modes for different applications with 4 terminal measurement for flexibility
Custom test	■	■	■	Adjustable current 10 – 110 A, ramp rates configurable from 0.5s upto 30s and configurable test duration for flexibility
Range and test mode rotary switches	■	■	■	Quick and easy selection of current ranges and test modes
Ultra tough outer case construction	■	■	■	Designed for use in demanding environments with a flame retardant UL94 V0 inner case for safety
Dual Ground™		■*	■*	Using the optional DC clamp enables circuit breaker testing with ground protection in place for safety
Large, clear LCD	■	■	■	Ideal for all light conditions, with backlight
Internal memory storage with USB download capability		■	■	For effective results management, up to 220 time and date stamped records
Remote Control			■	Control the instrument remotely over USB via a PC or laptop for added safety
Asset tagging			■	Running a PowerDB app on Windows tablet or smart phone to populate unique asset IDs for efficient asset management
Bluetooth®			■	For effective wireless communication. For download and asset tagging
* with optional Clamp				
All models. Two year warranty – second year conditional on free product registration.				

DLRO100 Series Digital low resistance ohmmeters

Display clearly showing large digits for test results and visible in all light conditions

Single button to save test results and to automatically save in auto mode

IP54 for protection against dust and rain during testing

Clearly visible C and P LED's showing continuity of current and potential connections

Back light - for low light conditions

USB and Bluetooth for communications

Rotary switch selection of test modes and off position

Simple navigation of setup and stored results

Rotary switch selection of view, download and delete test results

User configurable custom test.
Adjustable :
■ current ramp
■ duration of test
■ output current

Quick and easy rotary switch selection of 10 A, 50 A, 100 A tests - no configuration required



Smooth DC Output on C1 and C2 terminals


High noise immunity on P1 and P2 terminals

CAT IV 600 V AC / 500 DV safety rating on all terminals

DualGround™ capability with the DC clamp



A new terminal adapter has been designed to enable the use of users own test leads.



A user replaceable high power lightweight Li-ion battery provides, from a single charge, 200 Manual/Auto 100 A tests or up to two 10 minutes continuous 100 A tests and takes 2.5 hours to charge when fully discharged.

DLRO100 Series

Digital low resistance ohmmeters

ORDERING INFORMATION

Description	Order Code	Description	Order Code
DLRO100EB	1004-879	Optional Accessories	
DLRO100XB	1004-919	DLRO100 CAT IV 600 V Lead Set (16 ft)	1004-448
DLRO100HB	1004-959	DLRO100 CAT IV 600 V Lead Set (32 ft)	1004-449
Included Items		DLRO100 CAT IV 600 V Lead Set (49 ft)	1004-450
Certificate of Test		DLRO100 Terminal Adaptors (x2)	1005-555
Quick Start Guide		DLRO100 Lead Set Adaptors (10 A Leads)	1008-604
Calibration Certificate		DLRO100 CAT IV 600 V Kelvin Lead Set (16 ft)	1005-634
Mains lead		DLRO100 CAT IV 600 V Kelvin Lead Set (32 ft)	1005-635
Lithium Ion Battery Pack		DLRO100 CAT IV 600 V Kelvin Lead Set (49 ft)	1005-636
USB Cable (XB, HB variants only)		DLRO100 DC Clamp (MCPD 100L)	1005-622
		DLRO100 ISO17025 (UKAS) Calibration Certificate	1005-888
Lead set is NOT included with the instrument and must be ordered as an optional accessory.		DLRO100 Lithium Ion Battery Pack	1005-973
		USB Cable (XB, HB variants only)	1004-610
		Mains lead IEC320/US	1008-016

Contact:
 Industrial Process Measurement, Inc.
 3910 Park Ave. Unit #7
 Edison, NJ 08820 USA
 (732) 632-6400
 support@instrumentation2000.com
<https://www.instrumentation2000.com/>

DLRO100_DS_us_V11

ISO 9001
 The word 'Megger' is a registered trademark

Megger[®]