

VIDEO INSPECTION CAMERA

TECHNICAL DATA



FEATURES

- Comfortable pistol grip design and forward facing controls make it easy to detect and diagnose the unreachable
- High visibility 3.2" colour TFT LCD monitor with 320x240 pixel resolution
- 3.2' flexible gooseneck imager head retains configured shape and is waterproof (IP67)
- Gooseneck is expandable up to 30' with the optional cable extensions
- High visibility 10° adjustable LED lighting
- Camera and video functions allows you to save high resolution JPG images and live video
- TV compatible
- Transfer files to a computer via USB cable and optional 2GB SD memory card
- Rechargeable lithium-ion battery
- Includes video borescope, imager head, magnet, hook and mirror attachments, 3.7V lithium battery, DC power supply, USB cable, video output cable, user manual and hard carrying case

SPECIFICATIONS

- Viewing Distance:** 15 to 25cm (5.9 to 9.8")
- Viewing Angle:** 0 to 180°
- Photosensitive Device:** 1/4" CMOS
- LCD Monitor:** 640 x 480 pixels, 320 x 240 pixels max. resolution
- Max. Frames:** 30 FPS/S
- File Format Compatibility:** MPEG4, 3GP, AVI, ASF
- Image Format Compatibility:** JPEG
- Camera Video Format:** 3GP
- TV-OUT:** PAL/NTSC system
- Power Supply:** 3.7V, 2000mA Li-ion battery
- Camera Diameter:** 17mm (0.66"); Length: 1m (39")
- Dimensions:** 240 x 100x 160mm (9.5 x 3.9 x 6.3")

ORDERING INFORMATION

- BS-150..... Video Inspection Camera**
- SD-2GB2GB SD Memory Card**
- BS-C66' Cable Extension**
- BS-15-9C39mm Replacement Camera**
..... Head w/ 3' Cable
- BS-150/BATTERYReplacement Battery**

Contact:
Industrial Process Measurement, Inc.
3910 Park Avenue, Unit 7
Edison, NJ 08820
732-632-6400
support@instrumentation2000.com
<http://www.instrumentation2000.com>