

COMBUSTIBLE GAS DETECTOR

TECHNICAL DATA

FEATURES

- Heated semiconductor gas sensor
- Gases sensed: gasoline, propane, natural gas or fuel oil
- High-Low sensitivity selector
- Detects leaks as small as 5ppm of gasoline
- Ambient concentration reset function
- Audible and visual leak indications
- Flexible stainless steel probe
- Low battery indication and auto power off
- Includes reference leak source, batteries and hard carrying case

SPECIFICATIONS

Sensitivity: Variable, as low as 5 ppm (gasoline)

Alarm Settings: 7 LED tricolour bar indicator; variable intensity audible alarm

Warm-up Time: 90 seconds

Power Supply: 4 x 1.5V AA alkaline batteries

Battery Life: Approx. 40 hours continuous use

Probe Length: 400mm (15.5")

Dimensions: 21.7 x 6.6 x 5.6cm (8.5 x 2.6 x 2.2")

Weight: 400 g (14 oz)

ORDERING INFORMATION

C-383 Combustible Gas Detector
S-100B Replacement Sensor
CERTIGM1 NIST Calibration Certificate
C-383-NIST Gas Detector & NIST



Contact:
Industrial Process Measurement, Inc.
3910 Park Avenue, Unit 7
Edison, NJ 08820
732-632-6400
support@instrumentation2000.com
<http://www.instrumentation2000.com>