



TECHNICAL DATA

Features

- Calculates operating costs of household appliances
- Displays 8 important units of measure (Voltage, Current, Watts, Frequency, Power Factor, Energy used (kWh), Total Cost and Elapsed Time)
- Easy-to-read, dual LCD display
- Built-in battery backup
- Conforms to UL and CSA standards
- Includes battery

Specifications

Measuring Ranges:	Voltage: 100 to 150VAC 60Hz Current: 0 to 15A Power: 0 to 1800W Power Factor: 0 to 1.00 Frequency: 45 to 65Hz
Logging Ranges:	Energy: O to 9999kWh Cost: \$O to \$9999 Total Time: Omin to 9999days
Display:	Dual LCD
Display Update:	1 time/sec.
Overrange Indicator:	Yes
Power Supply:	1 x 3V (CR2032, back up battery)
Overvoltage Category:	Cat. II 150V
Product Certifications:	CE, ETL, Conforms to UL
	STD.61010-1, 61010-2-030;
	Certified to CSA STD.C22.2
	N0.61010-1, 61010-2-030
Operating Temperature:	32 to 122°F (O to 50°C)
Storage Temperature:	14 to 140°F (-10 to 60°C)
Operating Humidity:	10 to 90%
Dimensions:	5.1 x 2.6 x 1.5"
	(130 x 65 x 37mm)
Weight:	1.9 oz (155g)

ModelDescriptionR5090Power Meter



Contact:

Industrial Process Measurement, Inc. 3910 Park Avenue, Unit 7 Edison, NJ 08820 732-632-6400 support@instrumentation2000.com http://www.instrumentation2000.com