

Digital manifold

testo 557 - with external vacuum and Bluetooth

Measures high side / low side pressures and temperatures

Simultaneous, real-time super heat and sub-cooling

External vacuum probe for faster and more reliable evacuation of the system

App integration via Bluetooth for fast and convenient remote monitoring and reporting via email

Refrigerant updates to the instrument via App

60 on board refrigerant profiles

4-way valve block with 1/4 in. and 3/8 in. ports

3 year warranty with registration

psi/
barSuper
heatSub-
cooling

°F/°C

micron

Leak
Test

The testo 557 Digital Manifold opens up new possibilities for efficient analysis and documentation thanks to the integration of Bluetooth connectivity with the testo Refrigeration App. You can clearly read measurement data, such as automatic calculations of superheat, sub-cool and vacuum readings, on a Smartphone or Tablet, allowing you to work more quickly and conveniently than ever before. In addition, measurement reports can be created and sent directly from the job site.

The 557 features an external vacuum probe for faster and more reliable evacuations and is suitable for all refrigeration systems or heat pumps. This compact manifold has a 4-way valve block, large backlit display and sight glass. Two NTC thermistor clamp probes provide superior accuracy of simultaneous, real-time superheat and sub-cooling readings. With an optional 4 hose kit, the testo 557 is the complete solution for any air conditioning job you can throw at it.



Technical Data

testo 557

testo 557 kit, digital manifold with Bluetooth, 2 x clamp probes, external vacuum probe, batteries, case and certificate of conformity



Part no. 0563 1557

testo 557 with hoses

testo 557 kit, digital manifold with Bluetooth, set of (4) 60 inch refrigeration hoses, 2 x clamp probes, external vacuum probe, batteries, case and certificate of conformity



Part no. 0563 2557

Operating temperature	-4° to 122° F (-20 to +50 °C)
Storage temperature	-4° to 140° F (-20 to +60 °C)
Battery life (4 x AA Alkaline)	250 h (less with use of Bluetooth, backlight and vacuum)
Dimensions	8.7" x 4.0" x 2.75" (220 x 101 x 70 mm)
Weight	2.8 lb (1270 g)
Protection class	IP42 (splash proof)
Refrigerants in the instrument	60 profiles: R11, R12, R123, R1234yf, R1234ze, R125, R13B1, R134a, R14, R142B, R152a, R161, R22, R227, R23, R290, R32, R401A, R401B, R401C, R402A, R402B, R404A, R406A, R407A, R407B, R407C, R407D, R407F, R408A, R409A, R410A, R411A, R412A, R413A, R414B, R416A, R417A, R420A, R421A, R421B, R422A, R422B, R422C, R422D, R424A, R426A, R427A, R434A, R437A, R438A, R502, R503, R507, R508A, R508B, R600, R600a, R744 (CO ₂), R718 (H ₂ O), update via App
Warranty	2 years; 3 years with registration

Specifications

	Pressure	Temperature	Vacuum
Measuring range	-14.7 to 870 psi (-1 to 60 bar)	-58 to 302 °F (-50 to +150 °C)	0 to 20,000 Micron
Accuracy (at 70 °F)	±0.5 % fs	±0.9 °F (±0.5 °C)	±10% of rdg +10 microns (100 to 1000 microns)
Resolution	0.1 psi (0.01 bar)	0.1 °F (0.1 °C)	1 micron (from 0 to 1000 micron)
Connections	1/4", 3/8"	2 x plug-in (NTC probes)	External vacuum probe (DIN connection)
Overload	940 psi (65 bar)	-	-

Probes / Accessories

	Range	Accuracy	Part No.
Clamp probe for pipes to 1.38" diameter (35 mm), NTC, Fixed cable 4.9 ft. (1.5 m)	-40 to 257 °F (-40 to 125 °C)	±1.8 °F (-4 to 185 °F) ±1 °C (-20 to +85 °C)	0613 5505
Clamp probe for pipes to 1.38" diameter (35 mm), NTC, Fixed cable 16.0 ft. (5.0 m)	-40 to 257 °F (-40 to 125 °C)	±1.8 °F (-4 to 185 °F) ±1 °C (-20 to +85 °C)	0613 5506
Pipe wrap probe with Velcro for pipe diameter to max. 3" (75 mm), NTC, Fixed cable 4.9 ft. (1.5 m)	1.18" (30 mm) 11.80" (300 mm) -58 to 158 °F (-50 to +70 °C)	±0.4 °F (77 to 158 °F) ±0.2 °C (-25 to +70 °C) ±0.8 °F (-58 to -13 °F) ±0.4 °C (-50 to -25.1 °C)	0613 4611
Pipe clamp probe (NTC) for pipe diameters 0.2" to 2.5" (5 to 65 mm), Fixed cable 9 ft. (2.7 m)	-58 to 248 °F (-50 ... +120 °C)	±0.4 °F (77 to 176 °F) ±0.2 °C (-25 ... +80 °C)	0613 5605
External vacuum probe (DIN connection)	0 to 20,000 microns	±10% of rdg +10 microns (100 to 1,000 microns)	0638 1557
Transport case for testo 549/550/557 and accessories			0516 0012
Two-valve field replacement kit			0554 5570

Subject to change without notice.

07.2018