

RHDL60 Temperature and Humidity Datalogger

Record up to 16,000 readings each for Temperature and Humidity

Features:

- User adjustable sampling rate from 1 second to 24 hours
- High/Low Alarms with visual alert when settings are exceeded
- Min/Max records highest and lowest readings with date and time
- USB interface for transferring recorded data to your PC
- Includes 3.6V Lithium battery, USB cable, mounting bracket with combination lock and software CD

Applications:

Record Temperature and Humidity for long periods of time in virtually any indoor setting

Eliminate manual recording of data, monitor labs, greenhouses, warehouses, HVAC systems, storage areas, office space, classrooms, museums and more

Specifications

Temperature	-40 to 158°F (-40 to 70°C)
Accuracy	±1.8°F/1.0°C (+14 to 104°F/-10 to 40°C) ±3.6°F/2.0°C (all other ranges)
Relative Humidity	0 to 100%RH
Accuracy	±3.0%RH (40 to 60%) ±3.5%RH (20 to 40%/60 to 80%) ±5%RH (0 to 20%/80 to 100%)
Resolution	0.1°F/°C; 0.1%RH
Datalogging Points	16,000 Temperature 16,000 Humidity
Sampling Intervals	1sec to 24hr
PC Interface	USB
Power	3.6V Lithium Battery
Dimensions	3.7 x 1.9 x 1.2" (94.4 x 48.9 x 31.2mm)
Weight	3.2oz (90.7g)

Ordering Information:

RHDL60 Temperature and Humidity Datalogger
37-66 3.6V Lithium Battery, 2pk

