

TMP60 Dual Input Type K/J Thermometer

Large dual backlit display with °C, °F or °K temperature readout

Features:

- Display T1, T2, and T1-T2 differential readings
- Adjustable offset for probe compensation
- Min/Max/Average with elapsed time reference
- Data Hold freezes readings on the display
- Programmable auto power off with disable
- Optional model complete with Certificate of Traceability to N.I.S.T.
- Includes 3 AAA batteries and (2) Type K Thermocouple bead probes
- 1-year warranty



Applications:

For measuring the surface temperature of solid objects as well as in liquids and ambient temperature

Specifications

| | |
|--------------------------|---|
| Type K Temperature Range | -328 to 2501°F (-200 to 1372°C) |
| Type J Temperature Range | -346 to 2012°F (-210 to 1100°C) |
| Accuracy | ±(0.15% + 1.8°F/1°C) above -148°F (-100°C) ±(0.5% + 3.6°F/2°C) below -148°F (-100°C) |
| Resolution | 0.1°F/°C |
| Power | (3) AAA batteries |
| Dimensions | 8.7 x 2.5 x 1.1" (220 x 63 x 28mm) |
| Weight | 7oz (200g) |

Ordering Information:

TMP60 Dual Input Type K/J Thermometer
TMP60-NIST TMP60 with Certificate of Traceability to N.I.S.T.

NIST
TRACEABLE
CALIBRATION
AVAILABLE

RoHS **CE**